

LOAD SUPPORT

Recommended maximum width (mm) for correct load support					
Duty	Light duty	Light to medium	Medium duty	Heavy duty	Extra heavy duty
Reference	Density up to 800 kg/m ³ and lumps up to 20mm	Density up to 1200 kg/m ³ and lumps up to 50mm	Density up to 1600 kg/m ³ and lumps up to 100mm	Density up to 2400 kg/m ³ and lumps up to 250mm	Density up to 2400 kg/m ³ and lumps up to 250mm
160/2	600	450	300	Not recommended	Not recommended
200/2	750	600	450	Not recommended	Not recommended
250/2	900	750	750	400	Not recommended
250/3	1050	900	750	500	Not recommended
315/2	900	900	750	450	Not recommended
315/3	1200	1050	1050	750	450
315/4	1350	1200	1050	750	600
400/2	1200	1050	900	750	500
400/3	1200	1050	1050	750	500
400/4	1500	1500	1350	900	750
400/5	1800	1650	1500	1200	900
500/2	1200	1050	1050	750	600
500/3	1200	1050	1050	750	600
500/4	1650	1500	1500	1200	900
500/5	1800	1800	1800	1500	1350
630/2	1350	1350	1350	1200	1050
630/3	1650	1500	1500	1350	1200
630/4	1350	1200	1200	1050	900
630/5	1500	1350	1350	1200	1050
800/2	1350	1200	1200	1050	750
800/3	1800	1650	1500	1200	750
800/4	2200	1650	1500	1500	1200
800/5	1500	2500	2200	1800	1500
1000/3	2200	1650	1500	1200	1050
1000/4	2500	1800	1800	1500	1350
1000/5	2500	2500	2200	1800	1500
1250/3	2200	1800	1800	1350	1200
1250/4	2500	2200	2200	1650	1500
1250/5	2500	2500	2500	1800	1800
1600/4	2500	2500	1800	1800	1800
1600/5	2500	2500	2500	2200	1800

