

CHEVRON CONVEYOR BELT

APPLICATIONS

Chevron conveyor belts are designed to convey powdered, granulated, and small lump materials at gradients of up to 40 degrees. They are also suitable for conveying packaged goods.

SHAPE AND CHARACTERISTICS

- Available in various pattern designs, including those with “U” and “V” profiles.
- Patterned conveyor belts are composed of a belt carcass and a pattern. The pattern shape and height (depth) differ depending on the type of gradient required for the material being conveyed.

CHEVRON CONVEYOR BELT TYPES



TYPE – V6

Cleat Height: 6mm
Cleat Width: 400 – 1000mm
Pitch mm: 80mm
Belt Width: 500 – 1200mm



TYPE – V15

Cleat Height: 15mm
Cleat Width: 450mm
Pitch mm: 250mm
Belt Width: 500 – 1000mm



TYPE – OPEN V15

Cleat Height: 15mm
Cleat Width: 500mm
Pitch mm: 250mm
Belt Width: 500 – 1000mm



TYPE – Y17

Cleat Height: 17mm
Cleat Width: 550mm
Pitch mm: 330mm
Belt Width: 600 – 1200mm



TYPE – C25

Cleat Height: 25mm
Cleat Width: 750mm
Pitch mm: 330mm
Belt Width: 900 – 1200mm

